

FICHE DE DONNEES DE SECURITE

FDS 998 1187-ENG_10-2022

INFORMATIONS CONCERNANT LE FOURNISSEUR DE LA FDS:

Préparation:

Code produit: 998 1187

Désignation : Colorit, Colle activatrice Premium Bond pour métaux, 4 ml

Utilisation: Colle pour surface métallique

Identification de la Société:

Raison Sociale: Cookson-CLAL

Adresse siège social : 5 Chemin du Plateau 69570 Dardilly

Telephone: 0800 878 202

E-mail: qualite@cookson-clal.com

Numéro d'appel d'urgence :

N° ORFILA (INRS): + 33 (0)1 45 42 59 59 - http://www.centres-antipoison.net

Ce numéro permet d'obtenir les coordonnées de tous les centres Antipoison Français.

Ces centres antipoison et de toxicovigilance fournissent une aide médicale gratuite (hors coût d'appel), 24 heures

sur 24 et 7 jours sur 7.



Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Colorit Premium Bond
- · Article number:

81011794 81012486

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Not approved for private consumers.
- · Application of the substance / the mixture

Plastic - metal adhesives

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Heimerle + Meule GmbH Dennigstrasse 16 D-75179 Pforzheim

Telefon +49 (0) 7231 940-0 Telefax +49 (0) 7231 940-2199 www.heimerle-meule.com

· Further information obtainable from:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact - (Dangerous goods emergency number) +49 172 739 6970

· 1.4 Emergency telephone number:

DEUTSCHLAND - GERMANY:

Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)

(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111 ITALY:

Istituto Superiore di Sanità +3906499906140

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse 16662, (+342) 7914 794

LETTLAND - LATVIA:

Latvijas Vides, ģeoloģijas un meteoroloģijas centrs (+371) 670 32600

LITAUEN - LIETUVOS RESPUBLIKA:

Apsinuodijimų informacijos biuras +370 (85) 2362052



Version number 8 Revision: 13.10.2022 Printing date: 13.10.2022

Trade name: Colorit Premium Bond

(Contd. of page 1)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

acetone

10-Methacryl-oxydecyl-dihydrogenphosphat acetic acid

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P241 *Use explosion-proof [electrical/ventilating/lighting] equipment.*

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

(Contd. on page 3)



Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

Trade name: Colorit Premium Bond

(Contd. of page 2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.
- SECTION 3: Composition/information on ingredients
- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| Dangerous components / Information on ingredients: | | |
|---|--|------|
| CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49 | acetone; propan-2-one; propanone; 2-Oxopropane; 2-Propanone; beta-Ketopropane; Dimethyl ketone; Pyroacetic ether Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 | >90% |
| CAS: 64-19-7 EINECS: 200-580-7 Index number: 607-002-00-6 RTECS: AF 1225000 | acetic acid; acetic acid, of a concentration of more than 10 per cent, by weight, of acetic acid; Eastman Glacial Acetic Acid; Ethanoic acid; Ethylic acid; Glacial acetic acid; Methanecarboxylic acid Flam. Liq. 3, H226 Skin Corr. 1A, H314 Specific concentration limits: Skin Corr. 1A; H314: $C \ge 90\%$ Skin Corr. 1B; H314: $25\% \le C < 90\%$ Skin Irrit. 2; H315: $10\% \le C < 25\%$ Eye Irrit. 2; H319: $10\% \le C < 25\%$ | |
| CAS: 85590-00-7 | 10-Methacryl-oxydecyl-dihydrogenphosphat Skin Corr. 1B, H314 | <5% |

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 4)

Heimerle + Meule

Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

Trade name: Colorit Premium Bond

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment:



Wear self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Only handle and refill product in closed systems.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

he usual precautionary measures are to be adhered to when handling chemicals.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings.

Observe official regulations on storing packagings.

Prevent any seepage into the ground.

Information about storage in one common storage facility:

Store away from foodstuffs.

(Contd. on page 5)



Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

Trade name: Colorit Premium Bond

(Contd. of page 4)

· Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles. Store under lock and key and out of the reach of children.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.

| · Ingredients with limit valu | · Ingredients with limit values that require monitoring at the workplace: | | |
|-------------------------------|--|--|--|
| CAS: 67-64-1 acetone | | | |
| WEL (Great Britain) | Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm | | |
| IOELV (European Union) | Long-term value: 1210 mg/m³, 500 ppm | | |
| AGW (Germany) | Long-term value: 1200 mg/m³, 500 ppm 2(I);AGS, DFG, EU, Y | | |
| CAS: 64-19-7 acetic acid | | | |
| WEL (Great Britain) | Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm | | |
| IOELV (European Union) | Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm | | |
| AGW (Germany) | Long-term value: 25 mg/m³, 10 ppm 2(I);DFG, EU, Y | | |

· Regulatory information

WEL (Great Britain): EH40/2020

IOELV (European Union): (EU) 2019/1831

AGW (Germany): TRGS 900

· Ingredients with biological limit values:

CAS: 67-64-1 acetone

BGW (Germany) | 80 mg/l

Untersuchungsmaterial: Urin

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: Aceton

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· Respiratory protection:

Short term filter device:

Filter A

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

(Contd. on page 6)



Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

Trade name: Colorit Premium Bond

(Contd. of page 5)

according EN 14387 according to EN 143

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended. according to $EN\,374$

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

PVC gloves

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

Value for the permeation: Level ≤ 3

· Eye protection:



Tightly sealed goggles

according to EN 166

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Colourless
Odour: Acetone-like
Odour threshold: Not determined.

• pH-value at 20°C (68°F): 5–6

· Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 7)



Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

Trade name: Colorit Premium Bond

| | (Contd. of page |
|---|---|
| Initial boiling point and boiling range | e: >35°C (>95°F) |
| · Flash point: | < 23°C (< 73.4°F) |
| Flammability (solid, gas): | Highly flammable. |
| Ignition temperature: | 465°C (869°F) |
| Decomposition temperature: | Not determined. |
| · Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 2.6 Vol % |
| Upper: | 13 Vol % |
| Vapour pressure at 20°C (68°F): | 247 hPa (185.3 mm Hg) |
| Density: | Not determined. |
| · Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| Solvent content: | |
| Organic solvents: | >90 % |
| 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 values relevant for classification: | | | | |
|---|--------|--------------------|--|--|
| CAS: 67-6 | 64-1 a | acetone | | |
| Oral L | D50 | 5,800 mg/kg (rat) | | |
| Dermal L | D50 | 20,000 mg/kg (rbt) | | |

(Contd. on page 8)



Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

Trade name: Colorit Premium Bond

(Contd. of page 7)

CAS: 64-19-7 acetic acid

Oral | LD50 | 3,310 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Subacute to chronic toxicity:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- · 12.5 Results of PBT and vPvB assessment Not applicable.
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation





Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

· Waste disposal key:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself

(Contd. on page 9)



Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

Trade name: Colorit Premium Bond

(Contd. of page 8)

Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

| SECTION 14: Transport information | |
|---|---|
| 14.1 UN-Number ADR, IMDG, IATA | UN1090 |
| 14.2 UN proper shipping name ADR IMDG, IATA | UN1090 ACETONE ACETONE |
| 14.3 Transport hazard class(es) | |
| ADR, IMDG, IATA | |
| 3 | |
| Class Label | 3 Flammable liquids. 3 |
| 14.4 Packing group | 5 |
| ADR, IMDG, IATA | II |
| 14.5 Environmental hazards: Marine pollutant: | No |
| 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category | Warning: Flammable liquids. 33 F-E,S-D E |
| 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code | of Not applicable. |
| Transport/Additional information: | |
| ADR Limited quantities (LQ) Excepted quantities (EQ) | 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| Transport category | 2 |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) | 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| IATA | |
| Remarks: | 24h emergency contact - (Dangerous goods emergency number) |
| | +49 172 739 6970 |



Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

Trade name: Colorit Premium Bond

(Contd. of page 9)

· UN "Model Regulation":

UN 1090 ACETONE, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· GADSL - Global Automotive Declarable Substance List

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · National regulations:
- · Technical instructions (air):

| Class | Share in % |
|-------|------------|
| II | 1.0 |
| NK | 95.0 |

- · Waterhazard class: .
- · Other regulations, limitations and prohibitive regulations -
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Reasons for revise

If necessary, this saftey data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website www.heimerle-meule.com

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Department issuing SDS:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt

Department BASU - Construction / Occupational Safety / Environment

(Contd. on page 11)

Heimerle + Meule

Printing date: 13.10.2022 Version number 8 Revision: 13.10.2022

Trade name: Colorit Premium Bond

(Contd. of page 10)

sds@heimerle-meule.com

· Contact:

Herr Thomas Knuth

thomas.knuth@heimerle-meule.com

sds@heimerle-meule.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

GB ·