

FICHE DE DONNEES DE SECURITE

FDS 998 1195-ENG_12-2022

INFORMATIONS CONCERNANT LE FOURNISSEUR DE LA FDS:

Préparation:

Code produit: 998 1195

Désignation : Sel A pour bain de dégraissage avant rhodiage, Heimerle Meule, sachet de 1 kg

Utilisation: Cleaning material/ Detergent

Identification de la Société:

Raison Sociale: Cookson-CLAL

Adresse siège social: 5 Chemin du Plateau 69570 Dardilly

Telephone: 0800 878 202

E-mail: qualite@cookson-clal.com

Numéro d'appel d'urgence :

N° ORFILA (INRS): + 33 (0)1 45 42 59 59 - http://www.centres-antipoison.net

Ce numéro permet d'obtenir les coordonnées de tous les centres Antipoison Français.

Ces centres antipoison et de toxicovigilance fournissent une aide médicale gratuite (hors coût d'appel), 24 heures sur 24 et 7 jours sur 7.



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Electrolytic degreasing salt A Elektrolytisches Entfettungssalz Typ A
- · Article number:

86940800 86940810 81020482

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Not approved for private consumers.
- · Application of the substance / the mixture Cleaning material/ Detergent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Heimerle + Meule GmbH Dennigstrasse 16 D-75179 Pforzheim

Telefon +49 (0) 7231 940-0 Telefax +49 (0) 7231 940-2199 www.heimerle-meule.com

· Further information obtainable from:

 $Abteilung \ BASU-Bau/Arbeits sicherheit/Umwelt \\ Department \ BASU-Construction / Occupational \ Safety / Environment \\ sds@heimerle-meule.com$

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact - (Dangerous goods emergency number) +49 172 739 6970

· 1.4 Emergency telephone number:

DEUTSCHLAND - GERMANY:

Vergiftungs-Informations-Zentrale Freiburg, ++49 761 19240 (24 h)

(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

<u>IRELAND</u>

+353 1 809 2166 (7 Days 8 am -10 pm)

Healthcare Professionals: +353 1 809 2566

ITALY:

Istituto Superiore di Sanità (ISS) +3906499906140

Centro Antiveleni

Bergamo: +39 800 883300 Firenze +39 055 794 7819 Milano: +39 055 794 7819 Roma +39 06 68593726

Roma +39 06 49978000

Roma +39 06 3954343

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342 ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse

(Contd. on page 2)



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

(Contd. of page 1)

National (24/7): 16662 (+372) 7943 794 LETTLAND - LATVIA:

Valsts Toksikoloģijas centrs, Saindēšanās un zāļu informācijas centrs,

(24h) 112

(24h) + 371 67042473

LITAUEN - LIETUVOS RESPUBLIKA:

Poison Information Bureau (24/7), Tel.: +8 5 236 20 52

Apsinuodijimų informacijos biuras

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

sodium hydroxide

SODIUM METASILICATE PENTAHYDRATE

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

· Precautionary statements

P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

(Contd. on page 3)



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

(Contd. of page 2)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards Silicate containing elektrolytical degreasing, tensides

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components / Information on ingredients:			
CAS: 1310-73-2 EINECS: 215-185-5	sodium hydroxide; caustic soda Skin Corr. 1A, H314	50-100%	
Index number: 011-002-00-6	Specific concentration limits: Skin Corr. 1A; H314: $C \ge 5 \%$		
	Skin Corr. 1B; H314: 2 % ≤ C < 5 %		
	Skin Irrit. 2; H315: 0.5 % ≤ C < 2 %		
	Eye Irrit. 2; H319: $0.5 \% \le C < 2 \%$		
CAS: 10213-79-3	SODIUM METASILICATE PENTAHYDRATE	25-50%	
	Met. Corr.1, H290; Skin Corr. 1B, H314 STOT SE 3, H335		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after a accident or unwell

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth and then drink plenty of water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

A person vomiting while laying on their back should be turned onto their side.

Call a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Hazards Danger of gastric perforation.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB ·



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2. Do not use water.

Sand. Do not use water.

Extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents:



- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Only handle and refill product in closed systems.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

When diluting always pour product into water and not vice versa.

Provide suction extractors if dust is formed.

Thorough dedusting.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

he usual precautionary measures are to be adhered to when handling chemicals.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings.

(Contd. on page 5)



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

(Contd. of page 4)

Observe official regulations on storing packagings.

Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Store away from foodstuffs.

· Further information about storage conditions:

Keep container tightly sealed.

Store under lock and key and out of the reach of children.

- · Storage class: 8 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 1310-73-2 sodium hydroxide

WEL (Great Britain) Short-term value: 2 mg/m³

MAK (Germany) vgl.Abschn.IIb

· Regulatory information

WEL (Great Britain): EH40/2020 MAK (Germany): MAK- und BAT-Liste

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· Respiratory protection:

Filter P2

Short term filter device:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387

according to EN 143

· Hand protection

Alkaline resistant gloves

Check protective gloves prior to each use for their proper condition.

Preventive skin protection by use of skin-protecting agents is recommended.

(Contd. on page 6)



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

(Contd. of page 5)



according to EN 374

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· Material of gloves

Chloroprene rubber, CR

Recommended thickness of the material: ≥ 0.65 mm

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

Value for the permeation: Level ≤ 3

· For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Nitrile rubber, NBR

Chloroprene rubber, CR

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye/face protection



Tightly sealed goggles

according to EN 166

· Body protection:

Alkaline resistant protective clothing

Protective work clothing

- CD



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on	basic physical	l and chemical	properties

· General Information

Physical state
Colour:
Odour:
Mild

• Odour threshold: Not determined. • Melting point/freezing point: 1,390°C (34.590°F)

· Boiling point or initial boiling point and boiling

range Undetermined.
• Flammability Not determined.

· Lower and upper explosion limit

· Lower:
 · Upper:
 · Upper:
 · Not determined.
 · Flash point:
 · Decomposition temperature:
 · pH at 20°C (68°F)
 Not determined.
 12.9 (10%)

· Viscosity:

Kinematic viscosityDynamic:Not applicable.Not applicable.

·Solubility

· water: Soluble.

• Partition coefficient n-octanol/water (log value) Not determined. • Vapour pressure: Not applicable.

· Density and/or relative density

Density: Not determined.
Relative density Not determined.
Vapour density Not applicable.

· 9.2 Other information

· Appearance:

· Form: Powder

· Important information on protection of health and environment, and on safety.

environment, and on sajety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Solids content: 100.0 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void Void · Gases under pressure · Flammable liquids Void Void · Flammable solids · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water Void

(Contd. on page 8)



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

(Contd. of page 7)

Oxidising liquids
 Oxidising solids
 Organic peroxides

Void

· Corrosive to metals May be corrosive to metals.

· Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: Depends on the additives.
- · 10.3 Possibility of hazardous reactions

Reacts with acids.

Reacts with earth alkaline metals.

Reacts with acids, alkalis and oxidising agents.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Possible in traces.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
- · LD/LC50 values relevant for classification:

CAS: 1310-73-2 sodium hydroxide

Oral LD50 mg/kg (rat)

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · STOT-single exposure May cause respiratory irritation.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment Not applicable.
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

GB ·



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022


Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

(Contd. of page 8)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

· Waste disposal key:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3262
· 14.2 UN proper shipping name	
· ADR	UN3262 CORROSIVE SOLID, BASIC, INORGANIO
IMPC LATA	N.O.S. (SODIUM HYDROXIDE)
· IMDG, IATA	CORROSIVE SOLID, BASIC, INORGANIC, N.O. (SODIUM HYDROXIDE)
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· ADR, IMDĞ, İATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	80
· EMS Number:	F- A , S - B
Segregation groups	(SGG18) Alkalis
· Stowage Category	В



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

	(Contd. of page
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according instruments	ng to IMO Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	l kg
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 g
-	Maximum net quantity per outer packaging: 500 g
· Transport category	2
· IMDG	
· Limited quantities (LQ)	1 kg
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per outer packaging: 500 g
· Remarks:	
Temu is	24h emergency contact -
	(Dangerous goods emergency number)
	(and the determinant density in the desire)
	+49 172 739 6970
· UN "Model Regulation":	UN 3262 CORROSIVE SOLID, BASIC, INORGANIO
3	N.O.S. (SODIUM HYDROXIDE), 8, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

· GADSL - Global Automotive Declarable Substance List

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: .
- · Other regulations, limitations and prohibitive regulations -
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB



Printing date: 14.12.2022 Version number 13 (replaces version 12) Revision: 14.12.2022

Trade name: Electrolytic degreasing salt A

Elektrolytisches Entfettungssalz Typ A

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Reasons for revise

If necessary, this saftey data sheet can revised according to legal guidelines.

Our current version for your reference is available on our website www.heimerle-meule.com

· Relevant phrases

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

· Department issuing SDS:

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

· Contact:

Herr Thomas Knuth

thomas.knuth@heimerle-meule.com

sds@heimerle-meule.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals - Category 1

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

GB ·